



5-IN-1 PIPE FLASHING INSTALLATION INSTRUCTIONS

Important: Read Instructions Before Installation.

1. Determine the pipe size and match the pipe size with the correct tear line on the 5-in-1.
2. **DO NOT use a knife or sharp instrument to pierce or cut the 5-in-1 seal.** To create the pipe opening in the 5-in-1 seal, break the seal with a blunt object (a car key or ballpoint pen) and tear the material out by hand as shown below.



3. Carefully remove the shingles that will be used to cover the upper half of the 5-in-1 flange.
4. Place the flashing over and down the pipe, turning while applying downward pressure, until the flashing is in the desired position, flush against the roof deck.
5. Replace the shingles removed earlier, atop the flange.
6. The lowest part of 5-in-1 flange will lay on top of the shingles (as though it were a shingle).
7. Screw or nail the flange in place.
8. Secure shingles if required.
9. Adhere to installation requirements as determined by the regulatory authorities of your region.

Visit the Menzie's Metal Products' website for additional product information. Drawings, Specifications and Instructions are available for most products online at www.menzies-metal.com or scan the QR code.



Menzie's Metal Products

19370 60th Avenue, Surrey, BC V3S 3M2
800-665-8840 sales@menzies-metal.com
www.menzies-metal.com

More Than Just Metal

E. & O.E
01242014