



PLUMBING PIPE EXTENSION KIT INSTALLATION INSTRUCTIONS

Important: Read Instructions Before Installation.

1. Fit the one-piece pipe extension and adaptor into the existing pipe.
2. Secure with 3 self-tapping screws evenly spaced (not supplied).
3. Remove any debris or materials that may prevent the pipe flashing flange from laying flush against the deck.
4. Cut the extension pipe to 1/4" above the aluminum roof flashing.
5. Place the aluminum pipe flashing on the roof deck ensuring that metal flange is flush with roof surface.
6. Secure the flange to the roof deck using a minimum of 4 round head fasteners screwed into solid substrate. Fastening evenly spaced, 1" from edge of flange, is optimal.
7. Follow roofing system manufacturer's installation instructions for installing and flashing the roofing material to the aluminum pipe flashing.
8. Fit the aluminum cap on to the aluminum pipe flashing and extension pipe. Secure cap to pipe with a screw. Do not penetrate the pipe with the screw.
9. Adhere to installation requirements as determined by the regulatory authorities for your region.

Visit the Menzies Metal Products' website for additional product information. Drawings, Specifications and Instructions are available for most products online at www.menzies-metal.com or scan the QR code.



Menzies Metal Products

19370 60th Avenue, Surrey, BC V3S 3M2
800-665-8840 sales@menzies-metal.com
www.menzies-metal.com

More Than Just Metal

E. & O.E
01242014