



**TURBINE VENT (PITCHED ROOF)  
TURBINE VENT BASE FLAT GALVANIZED TO 3 1/2:12 PITCH  
TURBINE VENT TO 3 1/2:12 PITCH (FLAT ROOF)  
TURBINE VENT BASE FLAT SPUN (FLAT ROOF ONLY)  
INSTALLATION INSTRUCTIONS**

**Important: Read Instructions Before Installation.**

**\*\*\* Flat and pitched bases are ordered according to the required pitch.**

1. Match the size of the roof hole with the opening in the base of the Turbine Vent.
2. If installing on an existing roof, remove any debris or materials that may prevent the Turbine Vent flange from laying flush against the deck.
3. Place the Turbine Vent base on the roof deck and ensure that metal flange is flush with roof surface.
4. Secure the flange to the roof using a minimum of 4 round head fasteners into solid substrate. Fastening evenly spaced, 1" from edge of flange, is optimal.
5. Follow the roofing system manufacturer's installation instructions for installing and flashing the roofing material to the Turbine Vent.
6. Adhere to the installation requirements as determined by the regulatory authorities for your region.

Visit the Menzies Metal Products' website for additional product information. Drawings, Specifications and Instructions are available for most products online at [www.menzies-metal.com](http://www.menzies-metal.com) or scan the QR code.



**Menzies Metal Products**

19370 60<sup>th</sup> Avenue, Surrey, BC V3S 3M2  
800-665-8840 sales@menzies-metal.com  
www.menzies-metal.com

**More Than Just Metal**

E. & O.E  
01242014